

Camara G4 Bullet

DATASHEET UVC G4 BULLET



Cámara PoE interior/externo diseñada para proporcionar una vigilancia nocturna óptima.



Camera G4 Bullet

The UniFi Protect Camera G4 Bullet delivers clear 4MP, 24 fps video over Gigabit Ethernet. The ball joint mount design allows indoor or outdoor installation and offers flexible 3-axis adjustment. The camera has infrared LEDs with an automatic IR cut filter for day and night surveillance. It features a built-in microphone and supports 802.3af PoE mode A & mode B for power.



Mechanical

Dimensions	Ø75 x 140 mm (Ø2.95 x 5.51")
Weight	Without mount: 458 g (1.01 lb) With mount: 520 g (1.15 lb)
Enclosure material	Aluminum alloy
Mounting materials	Aluminum alloy, polycarbonate
Weatherproofing	IPX4
Resistance	IK04

Optics

Sensor	5 MP CMOS sensor
Lens	Fixed focal length
View angle	H: 86°, V: 60°, D: 111°
Night mode	Built-in light sensor Built-in IR LED illumination and IR cut filter

Video

Video compression	H.264
Resolution	2688 x 1512 (16:9)
Maximum frame rate	24 FPS
Image settings	Brightness, contrast, sharpness, saturation, noise reduction, 50/60 Hz

System

Processor specs	Quad core Arm® Cortex®-A53 based chip
Memory information	512 MB DDR3L
Management interface	UniFi Protect
Networking interface	GbE RJ45 port
Flash memory support	256 MB
Max. power consumption	4W
Power method	802.3af PoE
Button	Factory reset
Operating temperature	-20 to 40° C (-4 to 104° F)
Operating humidity	0 to 90% noncondensing
Certifications	FCC, IC, CE

Audio

Microphone Yes (can be disabled in software)

Software

Controller software UniFi Protect

Mobile apps UniFi Protect iOS and Android

